



Masonite Bullet Resistant Door Specifications

CORE TYPE	Fully Bonded Laminated Multilayer Core		
MAX OPENING SIZE	Single 4'0 x 10'0		
	Pair 8'0 x 10'0 – All pairs require BR Metal Edge / Astragal		
THICKNESS	Nonrated and 20-Minute 1-3/4"		
MACHINING	Prefit, Bevel and Factory Machining Required Contact sales for Machining Restrictions		
FACE	Wood Veneer, Laminates, MDO		
FINISHING	Factory Finishing Available		
FIRE RATING	20-Minute, Neutral Pressure and Positive Pressure B		
EDGE	Matching Banded Edges		
ENVIRONMENTAL	MR4 Recycled Content / MR5 Regional Materials / MR6 Rapidly Renewable MR7 Certified Wood / IEQ4 4-Low Emitting Materials (NAUF)		
LITE OPENING	Visible Max Size: 44" x 66" Minimum 6" Top Rail, 12" Bottom Rail, 6" Hinge Stile, and 8" Lock Stile Attacker Side - 2" wide – 7 gauge one piece construction Safe Side - 2" wide – 12 gauge welded construction		
SECURITY GLASS	UL 752 Bullet Resistant Glass – Factory Glazing Required Ballistic Level 3 Weight: 8.1 lbs. per square foot 72% Light Transmission		
METAL VISION FRAME	Bullet Resistant Vision Frame - UL 752 Listed Available in Beige, Gray, Dark Bronze, Polyester Powder Coat Custom colors available on request		
HARDWARE OPTIONS	BHMA Grades 1, 2, 3 Mortise Locks BHMA Grade 2 Cylindrical Locks		
WEIGHT	Level	3'0 x 7'0	4'0 x 7'0
	UL Level 1	211	282
	UL Level 2	228	304
	UL Level 3	245	327
WARRANTY	Limited 3-year Warranty (interior applications only)		
LABELING APPROVALS	Bullet Resistance Underwriters Laboratories		
FIRE APPROVALS	Guardian Fire Testing Laboratories		
STANDARDS	UL 752 Listed and Labeled Levels 1, 2, and 3		
	WDMA / AWI		